7/8" 圆形连接器（现场总线）ROUND PLUG CONNECTOR

现场接线
Field-wireable

螺钉压接
With screw terminals

插针 Male
直出线 Straight

插孔 Female
直出线 Straight

1 型号 Form

型号 Form No.	978101	978081	978221	978201
极数 Suppression	4-pole	5-pole	4-pole	5-pole

插针 Male
90°

插孔 Female
90°

型号 Form No.	978142	978141	978262	978261
极数 Suppression	4-pole	5-pole	4-pole	5-pole
电路图 Circuit diagram				
电缆出线直径 Clamping range screw thread	8…14mm			
针脚排序 Contact layout	插针 Male 	插针 Male 	插孔 Female 	插孔 Female 

2 技术参数 Technical data

额定电压 Supply voltage	600 V AC/DC
额定电流 Current per contact（40°C）	max. 8A
压线方式 Wiring method	螺钉压接 Screw terminals
防护等级 Protection	IP67– 插孔插针配合拧紧（EN 60529）When plugged and screwed down
温度范围 Temperature range	-25...+85°C
螺钉压线范围 Connection diameter	1.5mm^2

订货号 Part No.

可参考：1.0.1
Reference: 1.0.1

_ _ _ _ _ _	–	_ _ _	–	_ _ _ _
1 型号 Form				

备注 Notes

配件及技术参数页面 Accessories and technical page：1.3.8