

# Ethernet Cat. 5e 模块 MODULE



	型号 Type	订货号 Part No.		尺寸图 Drawing (mm)		
		公接插针 Male insert	母接插针 Female insert			
Ethernet Cat. 5e 模块 接线方式: 冷压针压接 Termination methods: Crimp terminal (冷压针请单独订购 Order crimp contacts separately)	屏蔽金属框 Shielding metal frame HM-M8-M	5140083016		M		
	屏蔽金属框 Shielding metal frame HM-M8-F		5140083116			
	屏蔽金属框含 2x4 接插体 2x4 contacts with additional shield connection to the hinged frame HM-M8-MSH	5140083216		F		
	屏蔽金属框含 2x4 接插体 2x4 contacts with additional shield connection to the hinged frame HM-M8-FSH		5140083316			
模块 Module	HM-MB-MI	5140013011		M		
	HM-MB-FI		5140013111	F		
线箱 Cable clamp	HM-CC 5-7 HM-CC 7-10 HM-CC 10-12	5030000141 5030000044 5030000143				

## 10A 插针 Contacts

### 技术参数 Technical data

材质: 铜镀银 / 金  
Material: Copper, hard silver / gold plated  
接触电阻 Contact resistance:  $\leq 3m\Omega$   
接线形式: 冷压接线  
Termination methods: Crimp connection


### DDM




### DDF



### 10A 公插针 Male



### 10A 母插针 Female



线径 Wire gauge(mm <sup>2</sup> )	接线长度 Stripping length	型号 Type	订货号 Part No.
0.14-0.37	AWG26-22 8.0mm	DDM-0.37	3150006124
0.5	AWG20 8.0mm	DDM-0.5	3150006123
0.75	AWG18 8.0mm	DDM-0.75	3150006125
1.0	AWG18 8.0mm	DDM-1.0	3150006122
1.5	AWG16 8.0mm	DDM-1.5	3150006121
2.5	AWG14 8.0mm	DDM-2.5	3150006126

线径 Wire gauge(mm <sup>2</sup> )	接线长度 Stripping length	型号 Type	订货号 Part No.
0.14-0.37	AWG26-22 8.0mm	DDF-0.37	3150006224
0.5	AWG20 8.0mm	DDF-0.5	3150006223
0.75	AWG18 8.0mm	DDF-0.75	3150006225
1.0	AWG18 8.0mm	DDF-1.0	3150006222
1.5	AWG16 8.0mm	DDF-1.5	3150006221
2.5	AWG14 8.0mm	DDF-2.5	3150006226