

# KEL 电缆引入系统 CABLE ENTRY SYSTEMS

## KEL E 可开式穿墙板



可分开穿芯 Split inserts

框架型号 Type	示意图 Description	开孔尺寸 (mm) Platemounting dimensions	KT 模块数量 Inserts 小 small / 大 large
<p>KEL-E2</p> <p>框架订货号 Part No. 99040602</p> <p>模块规格见 8.3.8–8.3.9 页 See page 8.3.8–8.3.9 module specifications</p>		43 × 24	2   -
<p>KEL-E3</p> <p>框架订货号 Part No. 99041103</p> <p>模块规格见 8.3.8–8.3.9 页 See page 8.3.8–8.3.9 module specifications</p>		65 × 24	3   -
<p>KEL E4</p> <p>框架订货号 Part No. 99041604</p> <p>模块规格见 8.3.8–8.3.9 页 See page 8.3.8–8.3.9 module specifications</p>		86 × 24	4   -
<p>KEL E5</p> <p>框架订货号 Part No. 99042405</p> <p>模块规格见 8.3.8–8.3.9 页 See page 8.3.8–8.3.9 module specifications</p>		112 × 24	5   -

材料 Material: 聚酰胺 Polyamide (PA)

阻燃等级 Flame class: UL94–V0, 自熄灭 Self-extinguishing

防护等级 Protection degree: IP54, 使用密封垫且正确选择穿芯规格 (符合 DIN EN 60529:2000–09)

With gasket and correct selection of the cable inserts

温度范围 Temperature: – 40°C to + 140°C (静态 Static)

特性 Properties: 无卤, 无硅 Halogen-free, silicone-free

KEL 高度 Height: 17 mm