

M23 连接器 ROUND PLUG CONNECTOR

现场接线
Field-wireable
6-pole
3+PE+4-pole
3+PE+5-pole

插孔 Female
直出线 straight



插孔 Female
90°



M23 动力连接器

| 1 型号 Form | No. | 923601 | 923801 | 923901 | 923411 | 923611 | 923822 | | | | | | | | | | | |
|---|--------------------------|--|---------------|---|----------|-------------------------------|--------------------|--------------|----------------|--------------------------|--------|----------------|--------------------------|--------|--------------------------|--------|----------|--|
| 极数 Suppression | | 6p(6xØ2) | 8p(4xØ2+4xØ1) | 9p(4xØ2+5xØ1) | 4p(4xØ2) | 6p(6xØ2) | 8p(4xØ2+4xØ1) | | | | | | | | | | | |
| 尺寸图 Description | | | | | | | | | | | | | | | | | | |
| 压线范围 Wire diameter | | 7-17mm | | | | | | | | | | | | | | | | |
| 针脚排序 Contact layout | | | | | | | | | | | | | | | | | | |
| 2 技术参数 Technical data | | 6p(6xØ2) | | 8p(4xØ2+4xØ1) | | 9p(4xØ2+5xØ1) | | | | | | | | | | | | |
| 额定电压 Supply voltage | | 630 V AC/DC | | 630 V (AC/DC) / 250 V (AC/DC) | | 630 V (AC/DC) / 250 V (AC/DC) | | | | | | | | | | | | |
| 额定电流 Current per contact | | 30A | | 30A / 10A | | 30A / 10A | | | | | | | | | | | | |
| 防护等级 Protection | | IP67- 插孔插针配合拧紧 When plugged and screwed down | | | | | | | | | | | | | | | | |
| 温度范围 Temperature range | | -20...+130°C | | | | | | | | | | | | | | | | |
| 测试电压 (两插针之间) Test voltage | | 6000V | | 6000V / 2500V | | 6000V / 2500V | | | | | | | | | | | | |
| 外壳材料 Housing material | | 锌合金压铸件 黄铜, 镀镍 Zinc alloy die casting Brass, nickel plating | | | | | | | | | | | | | | | | |
| 绝缘内嵌体材料 Insulation embedded body material | | PA66/PBT, UL 94/V0 | | | | | | | | | | | | | | | | |
| 接触件 (插孔) Contact element (female) | | Ø1mm | | <table border="1"> <thead> <tr> <th>类型 Type</th> <th>压线范围 Wire diameter</th> <th>订货号 Part No.</th> </tr> </thead> <tbody> <tr> <td>插孔 Female Ø1mm</td> <td>0.25~1.00mm²</td> <td>916431</td> </tr> <tr> <td rowspan="2">插孔 Female Ø2mm</td> <td>1.00~2.50mm²</td> <td>926201</td> </tr> <tr> <td>2.50~4.00mm²</td> <td>926221</td> </tr> </tbody> </table> | | 类型 Type | 压线范围 Wire diameter | 订货号 Part No. | 插孔 Female Ø1mm | 0.25~1.00mm ² | 916431 | 插孔 Female Ø2mm | 1.00~2.50mm ² | 926201 | 2.50~4.00mm ² | 926221 | Ø2mm | |
| 类型 Type | 压线范围 Wire diameter | 订货号 Part No. | | | | | | | | | | | | | | | | |
| 插孔 Female Ø1mm | 0.25~1.00mm ² | 916431 | | | | | | | | | | | | | | | | |
| 插孔 Female Ø2mm | 1.00~2.50mm ² | 926201 | | | | | | | | | | | | | | | | |
| | 2.50~4.00mm ² | 926221 | | | | | | | | | | | | | | | | |
| 订货号 Part No. | | | | | | | | | | | | | | | | | | |
| 可参考: 1.0.1 Reference: 1.0.1 | | ----- | | | | | | | | | | | | | | | | |
| | | 1 型号 Form | | | | | | | | | | | | | | | | |
| 备注 Notes | | 配件及技术参数页面 Accessories and technical page: 6.6.5 | | | | | | | | | | | | | | | | |