

M23 连接器 ROUND PLUG CONNECTOR



M23 圆形连接器
Round plug connector

现场接线
Field-wireable

6-pole

3+PE+4-pole

3+PE+5-pole

插针 Male 0°
法兰安装 Flange installation



插针 Male 90°
法兰安装 Flange installation



1 型号 Form	No.	923621	923821	923921	923641	923841	923941										
极数 Suppression		6p(6xØ2)	8p(4xØ2+4xØ1)	9p(4xØ2+5xØ1)	6p(6xØ2)	8p(4xØ2+4xØ1)	9p(4xØ2+5xØ1)										
尺寸图 Description																	
开孔尺寸																	
针脚排序 Contact layout																	
2 技术参数 Technical data		6p(6xØ2)		8p(4xØ2+4xØ1)	9p(4xØ2+5xØ1)												
额定电压 Supply voltage		630 V AC/DC		630 V (AC/DC) / 250 V (AC/DC)		630 V (AC/DC) / 250 V (AC/DC)											
额定电流 Current per contact		30A		30A / 10A		30A / 10A											
防护等级 Protection		IP67- 插孔插针配合拧紧 When plugged and screw down															
温度范围 Temperature range		-20...+130°C															
测试电压 (两插针之间) Test voltage		6000V		6000V / 2500V		6000V / 2500V											
外壳材料 Housing material		锌合金压铸件 黄铜, 镀镍 Zinc alloy die casting Brass, nickel plating															
绝缘内嵌体材料 Insulation embedded body material		PA66/PBT, UL 94/V0															
接触件 (插针) Contact element (male)		 Ø1mm		<table border="1"> <thead> <tr> <th>类型 Type</th> <th>压线范围 Wire diameter</th> <th>订货号 Part No.</th> </tr> </thead> <tbody> <tr> <td>插针 Male Ø1mm</td> <td>0.25~1.00mm²</td> <td>916331</td> </tr> <tr> <td rowspan="2">插针 Male Ø2mm</td> <td>1.00~2.50mm²</td> <td>926101</td> </tr> <tr> <td>2.50~4.00mm²</td> <td>926121</td> </tr> </tbody> </table>		类型 Type	压线范围 Wire diameter	订货号 Part No.	插针 Male Ø1mm	0.25~1.00mm ²	916331	插针 Male Ø2mm	1.00~2.50mm ²	926101	2.50~4.00mm ²	926121	
类型 Type	压线范围 Wire diameter	订货号 Part No.															
插针 Male Ø1mm	0.25~1.00mm ²	916331															
插针 Male Ø2mm	1.00~2.50mm ²	926101															
	2.50~4.00mm ²	926121															
订货号 Part No.		-----															
可参考: 1.0.1 Reference: 1.0.1		-----															
		1 型号 Form															
备注 Notes		配件及技术参数页面 Accessories and technical page: 6.6.5															