

# D-SUB 9/15 Pin 连接器

屏蔽 Shielded  
 压接或焊接  
 Crimp / solder pins  
 壳体规格 Size: Size1

插针 Male  
 180°



插孔 Female  
 180°



1 型号 Form 焊接式 Solder	900009	900315	901009	901315
	压接式 Crimp	900109		902009
极数 Suppression	9-pole	15-pole	9-pole	15-pole
电路图 Circuit diagram	插针 Male 9 Pin 	插针 Male 15 Pin 	插孔 Female 9 Pin 	插孔 Female 15 Pin 
压线范围 Wire diameter	6...8.7 mm			

2 技术参数 Technical data	
额定电压 Supply voltage	30V AC/DC
额定电流 Current per contact (40°C)	2A
温度范围 Temperature range	-25...+85 °C
压线方式 Wiring method	冷压压接 (冷压针见下表) Crimp terminal

针 Crimp contacts					
技术参数 Technical data 材质 Material: 铜镀银/金 Copper alloy silver/gold-plated 接触电阻 Contact resistance: ≤ 4 mΩ 接线形式 Terminal: 冷压接线 Crimp terminal	公插冲压针 Male 	冲压针 Stamped Contacts (500 pieces / 卷 reel)		车针 Machined Contacts (100 pieces / 包 pu)	
冲压针 Stamped Contacts 	母插冲压针 Female 	线径 Wire 0.09-0.25mm <sup>2</sup>	AWG 26-22	型号 Form SAM-13	订货号 Part No. 3 67 000 7167
车针 Machined Contacts 	公插车针 Male 	0.25-0.56mm <sup>2</sup>	22-20	SAM-33	3 67 000 8167
	母插车针 Female 	0.09-0.25mm <sup>2</sup>	26-22	SAF-13	3 67 000 7267
		0.25-0.56mm <sup>2</sup>	22-20	SAF-33	3 67 000 8267

备注 Notes

# D-SUB 9/15 Pin 连接器

屏蔽 Shielded  
压接或焊接  
Crimp / solder pins  
壳体规格 Size: Size1G

插针 Male  
45°



插孔 Female  
45°



1	型号 Form 焊接式 Solder	910009	910315	911009	911315
	压接式 Crimp	910109		912009	
	极数 Suppression	9-pole	15-pole	9-pole	15-pole
	电路图 Circuit diagram	插针 Male 9 Pin 	插针 Male 15 Pin 	插孔 Female 9 Pin 	插孔 Female 15 Pin 
	压线范围 Wire diameter	6~8.7 mm			

2	技术参数 Technical data
	额定电压 Supply voltage: 30V AC/DC
	额定电流 Current per contact (40°C): 2A
	温度范围 Temperature range: -25...+85 °C
	压线方式 Wiring method: 冷压压接 (冷压针见下表) Crimp terminal

## 针 Crimp contacts

### 技术参数 Technical data

材质 Material: 铜镀银/金

Copper alloy silver/gold-plated

接触电阻 Contact resistance: ≤ 4 mΩ

接线形式 Terminal: 冷压接线 Crimp terminal

### 冲压针 Stamped Contacts



### 车针 Machined Contacts



线径 Wire	AWG	冲压针 Stamped Contacts (500 pieces / 卷 reel)		车针 Machined Contacts (100 pieces / 包 pu)	
		型号 Form	订货号 Part No.	型号 Form	订货号 Part No.
0.09-0.25mm <sup>2</sup>	26-22	SAM-13	3 67 000 7167	DAM-13	3 67 000 5576
0.25-0.56mm <sup>2</sup>	22-20	SAM-33	3 67 000 8167	DAM-33	3 67 000 8576
0.09-0.25mm <sup>2</sup>	26-22	SAF-13	3 67 000 7267	DAF-13	3 67 000 5476
0.25-0.56mm <sup>2</sup>	22-20	SAF-33	3 67 000 8267	DAF-33	3 67 000 8476

备注 Notes