

M23 连接器 ROUND PLUG CONNECTOR

现场接线
Field-wireable
6-pole
3+PE+4-pole
3+PE+5-pole

插针 延长式连接器 Male Extended type connector



M23 动力连接器

1	型号 Form No.	923661	923881	923991																											
	极数 Suppression	6p(6xØ2)	8p(4xØ2+4xØ1)	9p(4xØ2+5xØ1)																											
	尺寸图 Description																														
	压线范围 Wire diameter	7-17mm																													
2	针脚排序 Contact layout																														
	技术参数 Technical data	<table border="1"> <tr> <td>额定电压 Supply voltage</td> <td colspan="3">630 V (AC/DC) / 250 V (AC/DC)</td> </tr> <tr> <td>额定电流 Current per contact</td> <td colspan="3">30A / 10A</td> </tr> <tr> <td>防护等级 Protection</td> <td colspan="3">IP67- 插孔插针配合拧紧 When plugged and screwed down</td> </tr> <tr> <td>温度范围 Temperature range</td> <td colspan="3">-20...+130°C</td> </tr> <tr> <td>测试电压 (两插针之间) Test voltage</td> <td colspan="3">2500V</td> </tr> <tr> <td>外壳材料 Housing material</td> <td colspan="3">锌合金压铸件 黄铜, 镀镍 Zinc alloy die casting Brass, nickel plating</td> </tr> <tr> <td>绝缘内嵌体材料 Insulation embedded body material</td> <td colspan="3">PA66/PBT, UL 94/V0</td> </tr> </table>			额定电压 Supply voltage	630 V (AC/DC) / 250 V (AC/DC)			额定电流 Current per contact	30A / 10A			防护等级 Protection	IP67- 插孔插针配合拧紧 When plugged and screwed down			温度范围 Temperature range	-20...+130°C			测试电压 (两插针之间) Test voltage	2500V			外壳材料 Housing material	锌合金压铸件 黄铜, 镀镍 Zinc alloy die casting Brass, nickel plating			绝缘内嵌体材料 Insulation embedded body material	PA66/PBT, UL 94/V0	
额定电压 Supply voltage	630 V (AC/DC) / 250 V (AC/DC)																														
额定电流 Current per contact	30A / 10A																														
防护等级 Protection	IP67- 插孔插针配合拧紧 When plugged and screwed down																														
温度范围 Temperature range	-20...+130°C																														
测试电压 (两插针之间) Test voltage	2500V																														
外壳材料 Housing material	锌合金压铸件 黄铜, 镀镍 Zinc alloy die casting Brass, nickel plating																														
绝缘内嵌体材料 Insulation embedded body material	PA66/PBT, UL 94/V0																														
接触件 (插针) Contact element (male)	<table border="1"> <tr> <td rowspan="2"> Ø1mm </td> <td>类型 Type</td> <td>压线范围 Wire diameter</td> <td>订货号 Part No.</td> </tr> <tr> <td>插针 Male Ø1mm</td> <td>0.25-1.00mm²</td> <td>916331</td> </tr> <tr> <td rowspan="2"> Ø2mm </td> <td rowspan="2">插针 Male Ø2mm</td> <td>1.00-2.50mm²</td> <td>926101</td> </tr> <tr> <td>2.50-4.00mm²</td> <td>926121</td> </tr> </table>			 Ø1mm	类型 Type	压线范围 Wire diameter	订货号 Part No.	插针 Male Ø1mm	0.25-1.00mm ²	916331	 Ø2mm	插针 Male Ø2mm	1.00-2.50mm ²	926101	2.50-4.00mm ²	926121															
 Ø1mm	类型 Type	压线范围 Wire diameter	订货号 Part No.																												
	插针 Male Ø1mm	0.25-1.00mm ²	916331																												
 Ø2mm	插针 Male Ø2mm	1.00-2.50mm ²	926101																												
		2.50-4.00mm ²	926121																												
订货号 Part No.																															
可参考: 1.0.1 Reference: 1.0.1																															
	1	型号 Form																													
备注 Notes	配件及技术参数页面 Accessories and technical page: 6.6.5																														