

KEL 电缆引入系统 CABLE ENTRY SYSTEMS

KEL 24 可开式穿墙板



可分开穿芯 Split inserts



框架型号 Type	示意图 Description	KT 模块数量 Inserts 小 small / 大 large
<p>KEL 24/10</p> <p>框架订货号 Part No. 99042241</p> <p>模块规格见 8.3.8-8.3.9 页 See page 8.3.8-8.3.9 module specifications</p>		10 / -
<p>KEL 24/7</p> <p>框架订货号 Part No. 99042247</p> <p>模块规格见 8.3.8-8.3.9 页 See page 8.3.8-8.3.9 module specifications</p>		6 / 1
<p>KEL 24/5</p> <p>框架订货号 Part No. 99042248</p> <p>模块规格见 8.3.8-8.3.9 页 See page 8.3.8-8.3.9 module specifications</p>		5 / -
<p>KEL 24/4</p> <p>框架订货号 Part No. 99042244</p> <p>模块规格见 8.3.8-8.3.9 页 See page 8.3.8-8.3.9 module specifications</p>		2 / 2

材料 Material: 聚酰胺 Polyamide (PA)
 阻燃等级 Flame class: UL94-V0, 自熄灭 Self-extinguishing
 防护等级 Protection degree: IP54, 使用密封垫且正确选择穿芯规格
 (符合 DIN EN 60529:2000-09)
 With gasket and correct selection of
 the cable inserts
 温度范围 Temperature: -40°C to +140°C (静态 Static)
 特性 Properties: 无卤, 无硅 Halogen-free, silicone-free
 开孔尺寸 Cut-out dimensions: 37 × 110 mm
 KEL 高度 Height: 17 mm

开孔尺寸 Platemounting dimensions

