







HM-RJ45 模块连接器 MODULAR CONNECTORS

额定电流 Rated current: 1 A 额定电压 Rated voltage: 50 V

	型号 Type	订货号 Part No.		尺寸图 Drawing (mm)
		公接插针 Male insert	母接插针 Female insert	
 HM-RJ45-M  HM-RJ45-4/8PIN  HM-RJ45-F	HM-RJ45-M	5140014632		
	HM-RJ45-4PIN HM-RJ45-8PIN	5454001100 5454001520		
	HM-RJ45-F		5140014721	

技术参数 Technical characteristics

1 插芯 Inserts

接插件针数 InsertsNumber of contacts	8
依据 DIN EN 61984 的电气数据 Electrical data	
- 额定电流 Rated current	1A
- 额定电压 Rated voltage	50V
- 额定脉冲电压 Rated impulse voltage	0.8kV
- 污染程度 Pollution degree	3
依据 UL 的额定 电压 Rated voltage	< 30V
传输特性	超 6 类可达 100MHz 依据 ISO/IEC 24 702 ISO/IEC 11 801
传输速率	10/100/1000 Mbit/s
绝缘电阻 Insulation resistance	$\geq 10^{10}\Omega$
材料 Material	聚碳酸酯 Polycarbonate
工作温度范围 Limiting temperatures	-40°C ...+125°C
依据 UL94 阻燃等级 Flammability	V0
可拔插次数 Mating cycles	≥ 500

HM-DM 模块连接器 MODULAR CONNECTORS

	型号 Type	订货号 Part No.	尺寸图 Drawing (mm)
堵头 Dummy module 用于填充框架上空白模块位 To fill up module spaces not in use in the frame 	HM-DM	5140009950	