



KEL 6 可开式穿墙板



可分开穿芯 Split inserts

框架型号 Type	示意图 Description	KT 模块数量 Inserts 小 small / 大 large
<p>KEL - 6/1</p> <p>框架订货号 Part No. 99040601</p> <p>模块规格见 8.3.8-8.3.9 页 See page 8.3.8-8.3.9 module specifications</p>		<p>- / 1</p>
<p>KEL - 6/4</p> <p>框架订货号 Part No. 99040604</p> <p>模块规格见 8.3.8-8.3.9 页 See page 8.3.8-8.3.9 module specifications</p>		<p>4 / -</p>

材料 Material: 聚酰胺 Polyamide (PA)
 阻燃等级 Flame class: UL94-V0, 自熄灭 Self-extinguishing
 防护等级 Protection degree: IP54, 使用密封垫且正确选择穿芯规格
 (符合 DIN EN 60529:2000-09)
 With gasket and correct selection of
 the cable inserts
 温度范围 Temperature: - 40°C to + 140°C (静态 Static)
 特性 Properties: 无卤, 无硅 Halogen-free, silicone-free
 开孔尺寸 Cut-out dimensions: 37 × 40 mm
 KEL 高度 Height: 17 mm

开孔尺寸 Platemounting dimensions

