

D-SUB 50 Pin 连接器

屏蔽 Shielded
 压接或焊接
 Crimp / solder pins
 壳体规格 Size: Size5



插针 Male
 180°









插孔 Female
 180°



1	型号 Form 焊接式 Solder	900050	901050
	压接式 Crimp	900150	902050

极数 Suppression	50-pole	50-pole
电路图 Circuit diagram	 <p>插针 Male 50 Pin</p>	 <p>插孔 Female 50 Pin</p>
压线范围 Wire diameter	8...11mm	

2	技术参数 Technical data
额定电压 Supply voltage	30V AC/DC
额定电流 Current per contact (40°C)	2A
温度范围 Temperature range	- 25...+ 85 °C
压线方式 Wiring method	冷压压接 (冷压针见下表) Crimp terminal

针 Crimp contacts																																							
技术参数 Technical data 材质 Material: 铜镀银 / 金 Copper alloy silver/gold-plated 接触电阻 Contact resistance: ≤ 4 mΩ 接线形式 Terminal: 冷压接线 Crimp terminal	公插冲压针 Male 	<table border="1"> <thead> <tr> <th rowspan="2">线径 Wire</th> <th rowspan="2">AWG</th> <th colspan="2">冲压针 Stamped Contacts (500 pieces / 卷 reel)</th> <th colspan="2">车针 Machined Contacts (100 pieces / 包 pu)</th> </tr> <tr> <th>型号 Form</th> <th>订货号 Part No.</th> <th>型号 Form</th> <th>订货号 Part No.</th> </tr> </thead> <tbody> <tr> <td>0.09-0.25mm²</td> <td>26-22</td> <td>SAM-13</td> <td>3 67 000 7167</td> <td>DAM-13</td> <td>3 67 000 5576</td> </tr> <tr> <td>0.25-0.56mm²</td> <td>22-20</td> <td>SAM-33</td> <td>3 67 000 8167</td> <td>DAM-33</td> <td>3 67 000 8576</td> </tr> <tr> <td>0.09-0.25mm²</td> <td>26-22</td> <td>SAF-13</td> <td>3 67 000 7267</td> <td>DAF-13</td> <td>3 67 000 5476</td> </tr> <tr> <td>0.25-0.56mm²</td> <td>22-20</td> <td>SAF-33</td> <td>3 67 000 8267</td> <td>DAF-33</td> <td>3 67 000 8476</td> </tr> </tbody> </table>		线径 Wire	AWG	冲压针 Stamped Contacts (500 pieces / 卷 reel)		车针 Machined Contacts (100 pieces / 包 pu)		型号 Form	订货号 Part No.	型号 Form	订货号 Part No.	0.09-0.25mm ²	26-22	SAM-13	3 67 000 7167	DAM-13	3 67 000 5576	0.25-0.56mm ²	22-20	SAM-33	3 67 000 8167	DAM-33	3 67 000 8576	0.09-0.25mm ²	26-22	SAF-13	3 67 000 7267	DAF-13	3 67 000 5476	0.25-0.56mm ²	22-20	SAF-33	3 67 000 8267	DAF-33	3 67 000 8476		
	线径 Wire	AWG	冲压针 Stamped Contacts (500 pieces / 卷 reel)			车针 Machined Contacts (100 pieces / 包 pu)																																	
型号 Form			订货号 Part No.	型号 Form	订货号 Part No.																																		
0.09-0.25mm ²	26-22	SAM-13	3 67 000 7167	DAM-13	3 67 000 5576																																		
0.25-0.56mm ²	22-20	SAM-33	3 67 000 8167	DAM-33	3 67 000 8576																																		
0.09-0.25mm ²	26-22	SAF-13	3 67 000 7267	DAF-13	3 67 000 5476																																		
0.25-0.56mm ²	22-20	SAF-33	3 67 000 8267	DAF-33	3 67 000 8476																																		
冲压针 Stamped Contacts 	母插冲压针 Female 																																						
车针 Machined Contacts 	公插车针 Male 																																						
	母插车针 Female 																																						

备注 Notes

D-SUB 连接器


D-SUB 50 Pin 连接器

屏蔽 Shielded
 压接或焊接
 Crimp / solder pins
 壳体规格 Size: Size5G



1	型号 Form 焊接式 Solder	910050	911050
	压接式 Crimp	910150	912050

极数 Suppression	50-pole	50-pole
-------------------	---------	---------



压线范围 Wire diameter	8...11mm
--------------------	----------

2 技术参数 Technical data

额定电压 Supply voltage	30V AC/DC
额定电流 Current per contact (40°C)	2A
温度范围 Temperature range	- 25...+ 85 °C
压线方式 Wiring method	冷压压接 (冷压针见下表) Crimp terminal


针 Crimp contacts

技术参数 Technical data
 材质 Material: 铜镀银 / 金
 Copper alloy silver/gold-plated
 接触电阻 Contact resistance: ≤ 4 mΩ
 接线形式 Terminal: 冷压接线 Crimp terminal

冲压针 Stamped Contacts



车针 Machined Contacts



线径 Wire	AWG	冲压针 Stamped Contacts (500 pieces / 卷 reel)		车针 Machined Contacts (100 pieces / 包 pu)	
		型号 Form	订货号 Part No.	型号 Form	订货号 Part No.
0.09-0.25mm ²	26-22	SAM-13	3 67 000 7167	DAM-13	3 67 000 5576
0.25-0.56mm ²	22-20	SAM-33	3 67 000 8167	DAM-33	3 67 000 8576
0.09-0.25mm ²	26-22	SAF-13	3 67 000 7267	DAF-13	3 67 000 5476
0.25-0.56mm ²	22-20	SAF-33	3 67 000 8267	DAF-33	3 67 000 8476

备注 Notes