



HA-003, HA-004 小型接插体 CONNECT THE SMALL BODY
















适配壳体 H3A, 详见 7.12.3 页 Suitable for H3A housing, see page 7.12.3

	型号 Type	订货号 Part No.		尺寸图 Drawing (mm)
		公接插针 Male insert	母接插针 Female insert	
接线方式: 螺钉压接 Termination methods: Screw terminal  M F 额定电流 Rated current: 10 A 额定电压 Rated voltage: 250 V 线规 Wire gauge: 0.5-2.5 mm ²	HA-003-M	1200032611		
	HA-003-F		1200032711	
接线方式: 弹片压接 Termination methods: Cage-clamp terminal  M F 额定电流 Rated current: 10 A 额定电压 Rated voltage: 400 V 线规 Wire gauge: 0.5-2.5 mm ²	HAS-003-M	1200032633		
	HAS-003-F		1200032733	
接线方式: 螺钉压接 Termination methods: Screw terminal  M F 额定电流 Rated current: 10 A 额定电压 Rated voltage: 250 V 线规 Wire gauge: 0.5-2.5 mm ²	HA-004-M	1200042611		
	HA-004-F		1200042711	
接线方式: 弹片压接 Termination methods: Cage-clamp terminal  M F 额定电流 Rated current: 10 A 额定电压 Rated voltage: 400 V 线规 Wire gauge: 0.5-2.5 mm ²	HAS-004-M	1200042633		
	HAS-004-F		1200042733	

HA 接插体

HA-010,HA-016,HA-032 小型接插体 CONNECT THE SMALL BODY

HA 接插体

	型号 Type	订货号 Part No.		尺寸图 Drawing (mm)
		公接插针 Male insert	母接插针 Female insert	
接线方式: 螺钉压接 Termination methods: Screw terminal  M F 额定电流 Rated current: 16 A 额定电压 Rated voltage: 250 V 线规 Wire gauge: 0.5-2.5 mm ² 适配 H10A 外壳, 详见 7.12.7 页 Suitable for H10A housing, see page 7.12.7	HA-010-M	1200102612		1) 接插体之间最大距离 24mm Distance for contact max. 24mm  M F 接插针排序 Contact arrangement  M F 面板安装开孔图 Panel cut out 
接线方式: 螺钉压接 Termination methods: Screw terminal  M F 额定电流 Rated current: 16 A 额定电压 Rated voltage: 250 V 线规 Wire gauge: 0.5-2.5 mm ² 适配 H16A 外壳, 详见 7.12.8 页 Suitable for H16A housing, see page 7.12.8	HA-016-M	1200162612		1) 接插体之间最大距离 24mm Distance for contact max. 24mm  M F 接插针排序 Contact arrangement  M F 面板安装开孔图 Panel cut out 
接线方式: 螺钉压接 Termination methods: Screw terminal  M F 额定电流 Rated current: 16 A 额定电压 Rated voltage: 250 V 线规 Wire gauge: 0.5-2.5 mm ² 适配 H32A 外壳, 详见 7.12.9 页 Suitable for H10A housing, see page 7.12.9	HA-016-M (1-16) HA-016-MD (17-32)	1200162612 1200162613		1) 接插体之间最大距离 24mm Distance for contact max. 24mm  M F 接插针排序 Contact arrangement  M F 面板安装开孔图 Panel cut out 
接线方式: 螺钉压接 Termination methods: Screw terminal  M F 额定电流 Rated current: 16 A 额定电压 Rated voltage: 250 V 线规 Wire gauge: 0.5-2.5 mm ² 适配 H32A 外壳, 详见 7.12.9 页 Suitable for H10A housing, see page 7.12.9	HA-016-F (1-16) HA-016-FD (17-32)		1200162812 1200162813	