


电缆旋紧件及各类电缆附件 CABLE GLANDS AND ACCESSORIES

名称 Identification	规格 (AG) Designation	D	L	B	H	型号 Type	订货号 Part No.
带内螺纹和外螺纹弯接头  材料 Material: 黄铜镀镍 Nickel plated brass O-ring 形密封圈: NBR 工作温度 Temperature range: -40°C to +100°C	M20×1.5	24	6.0	37	31	STUD-20-M	62320102
	M25×1.5	29	7.5	42	37	STUD-25-M	62325102
	M32×1.5	36	8.5	40	44	STUD-32-M	62332102
	M40×1.5	46	9.5	67	57	STUD-40-M	62340102
	M50×1.5	56	9.0	77	69	STUD-50-M	62350102

名称 Identification	覆盖率 Cover according	扩张范围 Ø (mm)	型号 Type	订货号 Part No.	包装规格 PU
可扩充编织网管 expandable braided sleeving in Polyester-Terephthalate  材料 Material: PET 覆盖率 Coverage: ≥ 70% 工作温度 Temperature range: -50 to +130°C 熔点 Melting point: +260°C 阻燃性 Flame class: 具有自行熄灭功能 (V2 UL94) 说明 Instructions: V2 UL94 DIN 5510 S4/SR2/ST2 NF F16-101 / F16-102 I2F2 不含卤素 使用说明 Directions for use: 编织网管一般按 1:2 的比例使用, 现已发展为铁路行业。	89%	3 ... 8	PET 4	63400410	100 m
	84%	4 ... 10	PET 5	63400510	100 m
	81%	6 ... 12	PET 6	63400610	100 m
	80%	8 ... 16	PET 8	63400810	100 m
	78%	10 ... 20	PET 10	63401010	100 m
	77%	12 ... 24	PET 12	63401210	50 m
	76%	15 ... 27	PET 15	63401510	50 m
	70%	19 ... 32	PET 20	63402010	25 m
	74%	24 ... 38	PET 25	63402510	25 m
	77%	28 ... 47	PET 30	63403010	25 m
	74%	40 ... 63	PET 40	63404010	25 m